

IN THE CLAIMS

The present listing of claims wholly replaces all previous listings of claims, and includes the status of all claims in the application.

1. (Cancelled)

2. (currently amended) A two-way asymmetric communication system having independently scalable upstream and downstream paths that enable remote data processor devices to communicate with a server, said system comprising:

a common routing/switching backplane for providing intercommunication services among multiple communication devices including said server,

an independent upstream controller in communication with said backplane operating in accordance with an upstream protocol for receiving information packets from said remote data processor devices, said upstream controller including network operating algorithms for analyzing response packets transmitted by said downstream controller to determine operational status of a first identified remote data processor device,

an independent downstream controller in communication with said backplane for transmitting data packets to said remote data processor devices in accordance with a downstream protocol, said independent downstream controller being operative to transmit control packets directed to a first identified remote data processor

device that instructs said device to respond with predetermined information in accordance with said control packet,

a network manager in communication with said independent upstream and downstream controllers through said backplane for effecting management of two-way communications between said first remote data processor device and a second remote data processor device, ~~devices~~ and said server; and

including multiple sub-channels in a downstream path and a bandwidth manager for dynamically balancing traffic loads in the downstream path in order to provide greater use of available downstream channels according to traffic conditions.

3. (previously presented) The two-way communication system as recited in claim 2 wherein said independent upstream and downstream controllers comprise separate and independent hardware components including interface cards mounted in a rack.

4. (previously presented) The two-way communication system as recited in claim 2 wherein said common switching/routing backplane comprises an Ethernet LAN hub.

5. (previously presented) The two-way communication system as recited in claim 2 wherein said downstream controller effects transmission of control packets that detect assignment of upstream transmit frequency utilized by a remote processor device, and said remote processor device assembles and transmits response packets which contain information indicative of the upstream transmit frequency being used by said remote processor device.

6. (currently amended) A two-way asymmetric communication system having independently scalable upstream and downstream paths that enable remote data processor devices to communicate with a server, said system comprising:

a common routing/switching backplane for providing intercommunication services among multiple communication devices including said server,

an independent upstream controller in communication with said backplane operating in accordance with an upstream protocol for receiving information packets from said remote data processor devices, said upstream controller including network operating algorithms for analyzing response packets transmitted by said downstream controller to determine operational status of a first identified remote data processor device,

an independent downstream controller in communication with said backplane for transmitting data packets to said remote data processor devices in accordance with a downstream protocol, said independent downstream controller being operative to transmit control packets directed to a first identified remote data processor device that instructs said device to respond with predetermined information in accordance with said control packet,

a network manager in communication with said independent upstream and downstream controllers through said backplane for effecting management of two-way communications between said first remote data processor device and a

second remote data processor device, ~~devices~~ and said server; and

wherein said downstream controller applies forward error correction to control packets transmitted on said downstream paths.

7. (previously presented) The two-way system as recited in claim 6 wherein said forward error correction includes Reed Solomon encoding and interleaving of information packets.

8. (Cancelled)

9. (currently amended) A two-way asymmetric communication system having independently scalable upstream and downstream paths that enable remote data processor devices to communicate with a server, said system comprising:

a common routing/switching backplane for providing intercommunication services among multiple communication devices including said server,

an independent upstream controller in communication with said backplane operating in accordance with an upstream protocol for receiving information packets from said remote data processor devices, said upstream controller including network operating algorithms for analyzing response packets transmitted by said downstream controller to determine operational status of a first identified remote data processor device,

an independent downstream controller in communication with said backplane for transmitting data packets to said remote data processor devices in accordance with a downstream protocol, said independent downstream controller being operative to transmit control packets directed to a first identified remote data processor device that instructs said device to respond with predetermined information in accordance with said control packet;

a network manager in communication with said independent upstream and downstream controllers through said backplane for effecting management of two-way communications between said first remote data processor device and a

second remote data processor device, ~~devices~~ and said server; and

wherein said network manager effects configuration management of said remote devices by effecting issuance of control packets that perform at least one of:

assigning an upstream response frequency; adjusting an upstream transmitter; assigning an IP address; assigning a local MAC address; assigning an upstream transmit data rate; effecting reporting of status; effecting a transmission of data by said remote processor devices; assigning a shared channel for use by said remote processor devices; and assigning a dedicated channel for use by said remote data processor device.

10 - 33. (Cancelled)

34. (currently amended)

In an asymmetric network having respective upstream and downstream communication paths for enabling a plurality of remote devices to receive information from a host over a shared medium, the improvement comprising:

plural downstream channels operating over said shared medium, and

a network manager for providing bandwidth management of downstream bandwidth allocated to respective remote devices over said plural downstream channels;

wherein said network manager further includes operative routines for detecting service requests for requested bandwidth, for assessing bandwidth utilization of respective downstream channels on said shared medium, and for assigning additional downstream bandwidth to remote devices in accordance with said utilization and service requests;

wherein said remote devices include operative routines for determining and gathering statistical data relating to operating characteristics thereof and for reporting said statistical data to said network manager, and wherein said network manager utilizes said reported statistical data for allocating upstream channels to said remote devices.

35. (cancelled)

36 - 63. (Cancelled)

64. (currently amended) An asymmetric network system including upstream and downstream channels and utilizing control and response packets for managing bandwidth and configuration parameters of multiple remote devices in communication with a host over a shared downstream medium, said network comprising:

a first controller located at a head end of said asymmetric network system, to generate a configuration control packet that contains control information for effecting at least one of upstream channel assignment, transmit power level, address assignment, and data transmission credit level,

a second controller located at the a head end of said asymmetric network ~~management~~ system to generate a bandwidth management control packet that effects allocation of bandwidth on said shared downstream medium to said remote devices, and

a third controller located at at least one of said remote devices that responds to said configuration control packet by transmitting information on said upstream channel in accordance with at least one of said upstream channel assignment, transmit power level, address assignment and data transmission credit level.

65. (Original) The asymmetric network system as recited in claim 64 wherein said first controller generates said configuration control packet according to registration information provided by a network operator including IP address assignment and account administration information.

66. (Original) The asymmetric network system as recited in claim 64 wherein said first controller generates said configuration control packet for a given remote device according to available unused channels, channel usage by other remote devices, available upstream bandwidth, bandwidth guaranteed to other remote devices, channel usage, class of service of said given remote device and requested demand for bandwidth of said given remote device.

67. (Original) The asymmetric network system as recited in claim 64 wherein said downstream medium comprises a wireless broadcast medium.

68. (Original) The asymmetric network system as recited in claim 64 wherein said downstream medium comprises a telephony return upstream channel.

69. (Original) The asymmetric network system as recited in claim 64 wherein said downstream medium comprises an RF broadcast and said upstream channel is carried in an RF transmission.

70 - 89. (Cancelled)

90. (currently amended) A remote device for use in an asymmetric network communication system which includes at least one high-speed downstream channel operating over a shared medium, said remote device comprising:

an RF interface for receiving high-speed data transmission over at least one of said downstream channels,

a microprocessor controller for receiving control packets from a network management system, said control packets including control information for effecting control of at least one of upstream channel assignment, transmitter level, remote address assignment, and transmission credit value allocated to said remote device, and

said microprocessor controller being responsive to said control packets to effect operation at said RF interface of at least one of said upstream channel assignment, transmit power level, remote address assignment and transmission credit value

wherein said microprocessor controller applies error correction to information packets which are transmitted upstream to said network management system.

91. (previously presented) The remote device as recited in claim 90 wherein said microprocessor controller confirms the operation of said remote interface at least one of said upstream channel assignment, transmit power level, remote address assignment and transmission credit value by returning a response packet to said network management system confirming said operation.

92. (Original) The remote device as recited in claim 90 further including operative routines for gathering statistical operational data about said remote device, and for reporting said statistical operating data to said network management system.

93. (Original) The remote device as recited in claim 90 wherein said microprocessor controller receives network operating software downloaded from said network management system, said network operating software being used for interpreting control packets to effect operation of said remote interface.

94. (Original) The remote device as recited in claim 90 wherein said microprocessor controller unencapsulates said control packets in order to decipher the information content thereof.

95. (Original) The remote device as recited in claim 90 further including an upstream transmit power responsive to said microprocessor controller for transmitting upstream data packets to said network management system.

96. (cancelled)

97. (Original) The remote device as recited in claim 90 further including a second RF interface for effecting the transfer of RF data signals in an upstream transmission to said network management system.

98. (Original) The remote device as recited in claim 90 further including a cable return interface for generating upstream information and response packets for transmission to said network management system.

99. (Original) The remote device as recited in claim 90 further including network operating software for use with a telephone return modem of a remote computer to effect transmission of upstream packets to said network management system.

100 - 104. (Cancelled)